



LFS-B-60

With three integrated cameras and video switcher controller.



Sensor specification

Parameter	Value
Maximal Detection Range (typical human with reflectivity $\geq 30\%$).	Up to 60 m
Maximal Detection Range for a Low (10%) Reflective Object	Max. 35 m
Angular Resolution	2 mR (0.115°)
Maximal Scanning Angle	100°
Beam Inclination Angle	0 \pm 0.5°
Adaptivity to Periodically Movement Objects (Trees, Bushes, etc.)	Yes
Scan Rate	5 \div 6 Hz
Pulse Repetition Frequency (PRF)	7 \div 8 kHz
Mounting Height	0-30m
CCD sensitivity	0.01Lux
*Video Output	Composite video 1V p-p @ 75 Ω
Output Interface	Dry contact / RS 485
Laser Safety Class	Class 1 (eye safe)
Wavelength	905nm
Operating Ambient Temperature	- 25°C \div + 50°C
Storage Temperature	- 35°C \div + 60°C
Supply Voltage	12VDC \pm 10% @ 1.4 A (17 Watt)
Installation position	Vertical / Horizontal
Enclosure rating	IP 67
**Weight	5 Kg
**Dimensions (W x D x H)	260 x 250 x 150 mm

*Default video standard - PAL-BG.

** Not include cover and bracket